

Glass Dry Erase Boards, Markerboards, and Whiteboards

CSI Specifications

Section 10 11 16.13 (Section 10115) Fixed Markerboards

(Section 10 11 00 / 10100 Visual Display Boards)

Impact Architectural Signs
26 E Burlington Ave
LaGrange, IL 60525

(708) 469-7178
[http://www.impactsigns.com/glass-whiteboard-dry-erase-board/
specifications@impactsigns.com](http://www.impactsigns.com/glass-whiteboard-dry-erase-board/specifications@impactsigns.com)

Part 1 – General

1.1 Section Includes

- A. Fixed , glass, dry-erase markerboards, whiteboards, dry erase boards, and magnetic whiteboards.

1.2 Scope

- A. Furnish glass panels , stand off hardware, and anchors as necessary.

1.3 Submittals

- A. Comply with Section 01330 (01 33 00) – Submittal Procedures.
- B. Product Data: Submit manufacturer's product data, including installation instructions.
Specifier Notes: Delete samples if not required.
- C. Samples: Submit manufacturer's sample of markerboards.
- D. Cleaning Instructions: Submit manufacturer's cleaning instructions.
- E. Warranty Documentation: Submit manufacturer's standard warranty.

1.4 Quality Assurance

- A. Manufacturer to have a minimum of 10 years experience producing glass markerboards.

Part II – Products

2.1 Acceptable Manufacturer

A. Impact Architectural Signs
26 E Burlington Ave
LaGrange, IL 60525

(708) 469-7178
specifications@impactsigns.com

B. Substitutes: Substitutes are not acceptable.

SPECIFIER NOTE: Edit the following paragraphs as required to specify the Cast Plaque applicable to the project. Delete those not required.

2.2 Product Information Cast Plaques

A. Material: ¼" thick tempered safety glass

B. Size

1. 24"x36"
2. 36"x48"
3. 36"x60"
4. 48"x60"
5. 48" x72"
6. 48" x 96:
7. Custom Size H x W inches

C. Finishes:

1. Clear
2. Frosted
3. Backpainted White
4. Backpainted black
5. Backpainted any specified PMS color
6. Magnetic (applies only with backpainted option)
7. Custom Frosted Watermark on 2nd surface

D. Mounting

1. Provide 1" diameter x ½ deep anodized aluminum peg mounting hardware (Qty 4-8 as needed determined by size)
2. Provide appropriate anchors to mount on drywall, concrete, or other surface.
3. Use only manufacturer approved and provided hardware

Part III – Execution

3.1 Installation

- A. A qualified installer shall install glass dry erase boards.
- B. Impact! Arcitectoral Signs offers installation nationwide for architectural signage.
- C. Install dry erase boards level, plumb, and at the height indicated

3.2 Cleaning

- A. Clean markerboards promptly after installation in accordance with manufacturer's instructions.
- B. Do not use harsh cleaning materials or methods that could damage surface.

3.2 Warranty

- A. Lifetime on surface finish

END OF SECTION